



#### SPECIFICATIONS:

HEATING -42000 BTU/H (AT 150°F T.D)  
 AIRFLOW -500 CFM  
 CURRENT -11.6 AMPS (AT 12V)  
 WEIGHT -18.5 LBS.

#### 2-SPEED OPERATED MOTORS

THE HEATER COIL IS REVERSIBLE FOR LEFT HAND CONNECTION.

CASING MADE OF 18GA. CRS. AND FINISHED IN BLACK SEMI-GLOSS EPOXY POWDER COAT.

13	2	SPRING GRIP RETAINER
12	2	SNAP IN PLUG
11	2	SNAP IN PLUG
10	1	GROMMET
9	2	FAN
8	2	MOTOR BRACKET
7	2	MOTOR 12V
6	1	HEATER COIL
5	2	COIL SUPPORT
4	1	COVER
3	1	FRONT
2	1	GRILL
1	1	CASING
SYM	PCS	DESCRIPTION

NUMERO DE PIÈCE/PART NUMBER	DESCRIPTION			
<b>805-504</b>	Chaufferette 12V - 11.6 Amp / Heater 12V - 11.6 Amp			
DESSIN PAR/DRAWING BY	BTU - CFM		CONNECTION	
Jimexs	42,000 BTU - 500 CFM		Arrière / Rear	
JIMEXS.COM / INFO@JIMEXS.COM	DATE	FEUILLE/SHEET	ÉCHELLE/SCALE	PROJECTIONS
	2015-08-07	1/1	NAE	

