



Finition: Plaqué zinc-électrique brillant
Hauteur: 3.00" (76.2mm)
Capacité: 300-500 livres
Longueur: 10" - 60" (254.0mm - 1524.0mm)
Course: Pleine course
Option: Conforme aux normes RoHS

Finish: Bright electro-zinc (c) plating
Height: 3.00" (76.2mm)
Loading: 300-500 pound class
Length: 10" - 60" (254.0mm - 1524.0mm)
Travel: Full Travel
Option: RoHS compliant

Intermediate

Model	I (mm)	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	J (mm)	K (mm)	M (mm)	N (mm)	P (mm)	Q (mm)	R (mm)	S (mm)	
323-510	254	254							103.1	128.5	147.6	166.6				152.4	209.6	228.6	
323-512	304.8	304.8							153.9	179.3	198.4	217.4				203.2	260.4	279.4	
323-514	355.6	355.6							204.7	230.1	249.2	269.2				254	311.2	330.2	
323-516	406.4	406.4	127						255.5	280.9	299.9	319				304.8	361.9	381	
323-518	457.2	457.2	127						246.1	306.3	331.7	350.8	369.8			355.6	412.8	431.8	
323-520	508	508	127	190.5					296.9	357.1	382.5	401.6	420.6			406.4	463.6	482.6	
323-522	558.8	558.8	127	190.5					347.7	407.9	433.3	452.4	471.4			457.2	514.4	533.4	
323-524	609.6	609.6	127	190.5					398.5	458.7	484.1	503.2	522.2			508	565.2	584.2	
323-526	660.4	660.4	127	190.5					449.3	509.5	534.9	553.9	573			558.8	615.9	635	
323-528	711.2	711.2	127	190.5					500.1	560.3	585.7	604.8	623.8			609.6	666.8	685.8	
323-530	762	762	127	190.5	368.3				550.9	611.1	636.5	655.6	674.6	235	501.6	660.4	717.6	736.6	
323-532	812.8	812.8	127	190.5	368.3				601.7	661.9	636.5	655.6	674.6	235	501.6	660.4	717.6	736.6	
323-534	863.6	863.6	127	190.5	368.3	469.9			652.5	712.7	738.1	757.2	776.2	235	419.1	603.3	762	819.2	787.4
323-536	914.4	914.4	124	190.5	368.3	520.7			703.3	763.5	788.9	808	827	235	444.5	654.1	812.8	870	889
323-538	965.2	965.2	127	190.5	368.3	520.7			754.1	814.3	839.7	858.8	877.8	235	469.9	704.9	863.6	920.8	939.8
323-540	965.2	965.2	127	190.5	368.3	520.7			804.9	865.1	890.5	909.6	928.6	235	495.3	755.7	914.4	971.6	990.6
323-542	1066.8	1066.8	127	190.5	368.3	520.7	723.9		855.7	915.9	941.3	960.4	979.4	235	520.7	806.5	965.2	1022.4	1041.4
323-544	1160	1160	127	190.5	368.3	520.7			906.5	966.7	992.1	1011.2	1030.2	235	546.1	857.3	1016	1073.2	1092.2
323-548	1219.2	1219.2	127	190.5	368.3	520.7	825.5	1008.1	1058.3	1093.7	1112.78	1131.8	1150.8	235	596.9	958.8	1117.6	1174.8	1193.8
323-560	1524	1524	127	190.5	368.3	520.7	825.5	1312.9	1373.1	1398.5	1417.6	1436.6	1455.6	235	596.9	958.8	1422.4	1479.6	1498.6

Model	L ^{+0.3} -0.3 (mm)	A ^{+0.5} -0.5 (mm)
323-510	246.5	85
323-512	297.3	95.2
323-514	348.1	120.6
323-516	398.9	146
323-518	449.7	171.4
323-520	500.5	196.8
323-522	551.3	222.2
323-524	602.1	247.6
323-526	652.9	273
323-528	703.7	298.4
323-530	754.5	323.8
323-532	805.3	349.2
323-534	856.1	374.6
323-536	906.9	400
323-538	957.7	425.4
323-540	1008.5	450.8
323-542	1059.3	476.2
323-544	1110.1	501.6
323-548	1160.9	527
323-560	1516.5	704.8